F3 V050 TAIL-LIFT FOR PANEL VANS - 2 CYLINDERS



load capacity: 500 kg



Load Capacity	500 kg
Voltage	12 V
Max Power Consumption	130 Amp
Max Pressure Valve Setting	140 bar
Up-stroke Speed (Full Load)	5 m/min
Down-stroke Speed (Full Load)	8 m/min
Oil Tank Capacity	2 litres
Noise Level	< 70 dB
Electric Motor Power	1600 Watt
Standard Platform Depth	1400 mm - 1600 mm
Standard Platform Width	1450 mm
Weight for Complete Tail-lift with Platform Depth 1400 mm	179 kg
Weight for Complete Tail-lift with Platform Depth 1600 mm	185 kg
Mounting	Bolted assembly plates
Platform Opening	Powered opening of the platform with 1 double-acting tilting cylinder

APPLICATIONS

The completely new cantilever tail-lift F3 V050 has been designed and built for the 3.5 ton panel van range and can be installed easily without modifications to the host vehicle. Installation is made quick and easy with individual mounting brackets for most vans. F3 V050 is especially designed for: Citroen JUMPER / RELAY Fiat NEW DUCATO Ford NEW TRANSIT Iveco DAILY Mercedes NEW SPRINTER Mercedes VITO Nissan INTERSTAR Nissan PRIMASTAR Opel MOVANO VIVARO Opel Peugeot BOXER Renault MASTER Renault TRAFFIC VolksWagen CRAFTER VolksWagen TRANSPORTER

All hydraulic steel parts are treated with KTL hexacrylic electro-cataphoresis

Bolted assembly plates